

Datasheet



EXM800

Expansion module EXM800

Expansion module EXM800 has 8 terminals, which can be programmed as a combination of inputs (zones) and outputs (PGM). Maximum 8 zones or 7 PGM plus 1 zone can be programmed.



Features	EXM800
Description	Zone & PGM module
Product type	Alarm system module
On-Board zones	Up to 8
On-Board (open collector type) PGM	Up to 7 (depends on selected zones)
Data bus protocol	KRBUS
Zone loop (detector) type	NC, NO, NC/EOL, NO/EOL, NC/DEOL, NO/DEOL
Maximum wiring distance to CP	300 m
Power supply	9 - 14 V
Voltage measurement on module	Yes
Current consumption	15 mA
Maximum current into -PGM	-0.075 A
Maximum total current into all -PGM's	-0.5 A
Overall dimensions W x H in mm	67 x 50
Environmental compliance	ROHS
Operating temperature	Nuo -10°C iki +50°C
Production status	In production

SECOLink

EASY TO INSTALL, EASY TO USE



ΗΛΚΑ Α.Ε.

ΙΔΙΩΤΙΚΗ ΕΠΙΧΕΙΡΗΣΗ ΠΑΡΟΧΗΣ ΥΠΗΡΕΣΙΩΝ ΑΣΦΑΛΕΙΑΣ
Αρ. Αδείας Λειτουργίας Υπ. Δημοσίας Τάξης 3015/39/60/97-μγ

Τεμπών 14, 153 42, Αγ. Παρασκευή Αττικής
Τηλ.: 210-6071510, Fax: 210-6071599

sales@ilka.gr

www.ilka.gr

www.ilka.gr/products

