

Premium touch screen for your home

The Akuvox C313W multifunctional communicator, with a Linux operating system, provides audio and video communication with door phones via SIP 2.0 protocol. It delivers the ultimate touch screen experience in an unobtrusive, space-saving design featuring a brilliant 7-inch capacitive touch screen display.

At a Glance

- Ultra-clear, stylish appearance;
- Thin profile and small footprint;
- Linux OS;
- 7-inch capacitive touch screen with energy saving mode;
- Two-way audio communication with other units in the network;
- Powered by PoE or external source;
- Support US or European electrical wall box mounting;
- Complies with SIP standard for easy integration in every SIP capable PBXes;



Physical & Power

- | | |
|--|--|
| • Front panel: Plastic | • Microphone: Single microphone |
| • RAM / ROM: 64MB / 128MB | • Speaker: Single speaker |
| • Display: 7 Inch TFT LCD | • Ethernet ports: 2xRJ45 |
| • Screen: 7 Inch capacitive touch screen | • POE: 802.3af Power-over-Ethernet |
| • Wi-Fi: IEEE802.11 b/g/n, @2.4GHz | • Power: 12V DC connector |
| • RS485 Port: 1 | • Tamper Resistant: Support |
| • Relays Out: 1 | • Installation: Wall-mounted & Desktop |
| • Bell in: 1 | • Dimension: 200.2x132.2x27.2mm |
| • Alarm Input: 8 | • Working Humidity: 10~90% |
| | • Working Temperature: -10°C ~ +45°C |
| | • Storage Temperature: -20°C ~ +70°C |