

CRM-2H UNI



Specifications

ETI Code	002470003
Description	CRM-2H UNI
Class name	Time relay
Voltage type	AC/DC
Number of contacts	1
Number of CO contacts	1
function	Time relay
Maximum load capacity at AC1 (VA)	4000VA
Number of functions	2
Supply voltage (V)	12V-240V
Rated current (A)	16A

Online product page [🔗](#)

Other documentation







- Description
- Technical data catalogue
- 3D Model
- 2D File
- Instruction manual
- CE declaration
- Eplan file

ETIM international classification


Classification	EC001669
Class name	Timer relay for distribution board
Type of excitation	Digital with single function
Function	On/off-switch wiping relay
1st interval unit	Minutes/hours
1st interval	0.02...2400
2nd interval unit	Minutes/hours
2nd interval	0.02...2400
Mounting method	DIN rail
Width in number of modular spacings	1
Built-in height	65mm
Number of changeover switches	1
Control voltage 1	12...12V
Type of control voltage 1	AC/DC
Frequency control voltage 1	50...50Hz
Control voltage 2	240...240V
Type of control voltage 2	AC
Frequency control voltage 2	50...60Hz
Voltage type (supply voltage)	AC/DC
Nominal switching current at 250 V AC	16A

Dimension drawing



Symbol/Connection

Perioda začne z impulzom



Perioda začne s premorom

