

R 20-20 230V



Specifications

ETI Code	002461210
Description	R 20-20 230V
Class name	Modular contactor
Rated operational current I_e AC-1/AC-7 (A)	20A
Rated operational voltage AC (V)	250V
Rated AC control circuit voltage U_c (V)	230V
Type	AC
Rated Frequency (Hz)	50Hz/60Hz
Number of NO contacts	2
function	Modular contactor
Mounting type	DIN rail
Catalogue Group	Type R

Online product page [🔗](#)

Other documentation



3D Model

2D File

CE declaration

Eplan file

ETIM international classification

Classification	EC001653
Class name	Installation contactor for distribution board
Rated operating voltage	230...400V
Rated operation current	20A
Rated excitation voltage	230...230V
Voltage type (operating voltage)	AC
Voltage type (excitation voltage)	AC
Number of contacts as normally open contact	2
Max. incandescent lamp load	2160W
Max. load fluorescent lamp	935VA
Max. load fluorescent lamp (Duo circuit)	2320VA
Max. load fluorescent lamp (parallel compensated)	1020VA
Slider for hand switch	No
Number of modular spacings	1
Built-in depth	60mm
Additional equipment possible	No
Degree of protection (IP)	IP20

Dimension drawing

R20
165,150

