

# R 25-40 230V



## Specifications

ETI Code	002462310
Description	R 25-40 230V
Class name	Modular contactor
Rated operational current $I_e$ AC-1/AC-7 (A)	25A
Rated operational voltage AC (V)	440V
Rated AC control circuit voltage $U_c$ (V)	230V
Type	AC
Rated Frequency (Hz)	50Hz/60Hz
Number of NO contacts	4
function	Modular contactor
Mounting type	DIN rail
Catalogue Group	Type R

Online product page [🔗](#)

## Other documentation



3D Model

2D File

CE declaration

Eplan file

## ETIM international classification

Classification	EC001653
Class name	Installation contactor for distribution board
Rated operating voltage	230...400V
Rated operation current	25A
Rated excitation voltage	230...230V
Voltage type (operating voltage)	AC
Voltage type (excitation voltage)	AC
Number of contacts as normally open contact	4
Max. incandescent lamp load	3000W
Max. load fluorescent lamp	1190VA
Max. load fluorescent lamp (Duo circuit)	2552VA
Max. load fluorescent lamp (parallel compensated)	1360VA
Slider for hand switch	No
Number of modular spacings	2
Built-in depth	60mm
Additional equipment possible	Yes
Degree of protection (IP)	IP20

## Dimension drawing

