



 PRODUCT-DETAILS

AF12-30-10-11

AF12-30-10-11 24-60V50/60HZ 20-60VDC Contactor



General Information

Extended Product Type:	AF12-30-10-11
Product ID:	1SBL157001R1110
EAN:	3471523110311
Catalog Description:	AF12-30-10-11 24-60V50/60HZ 20-60VDC Contactor
Long Description:	<p>The AF12-30-10-11 is a 3 pole - 690 V IEC or 600 UL contactor with 1 built-in auxiliary contact and screw terminals, controlling motors up to 5.5 kW / 400 V AC (AC-3) or 7-1/2 hp / 480 V UL and switching power circuits up to 28 A (AC-1) or 28 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (24-60 V 50/60 Hz and 20-60 V DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p>
Display Name:	AF12-30-10-11

Ordering

Minimum Order Quantity:	1 piece
--------------------------------	---------

Customs Tariff Number: 85364900

Popular Downloads

EPLAN Data:	9AAC159646_EPLAN
Data Sheet, Technical Information:	1SBC100214C0202
Instructions and Manuals:	1SBC101027M6801
Instructions and Manuals (Part 2):	1SAC200017M0002
CAD Dimensional Drawing:	2CDC001079B0201

Dimensions

Product Net Width:	45 mm
Product Net Depth / Length:	77 mm
Product Net Height:	86 mm
Product Net Weight:	0.27 kg

Technical

Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	0
Number of Poles:	3P
Standards:	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60335-2-40 LZGH2 A2L, UL 60947-4-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 60947-4-1
Rated Operational Voltage:	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f):	Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ }^\circ\text{C}$ 35 A acc. to IEC 60947-5-1, $\Theta = 40\text{ }^\circ\text{C}$ 16 A
Rated Operational Current AC-1 (I_e):	(690 V) 40 $^\circ\text{C}$ 28 A (690 V) 60 $^\circ\text{C}$ 28 A (690 V) 70 $^\circ\text{C}$ 24 A
Rated Operational Current AC-3 (I_e):	(415 V) 60 $^\circ\text{C}$ 12 A (440 V) 60 $^\circ\text{C}$ 12 A (500 V) 60 $^\circ\text{C}$ 12.5 A (690 V) 60 $^\circ\text{C}$ 9 A (380 / 400 V) 60 $^\circ\text{C}$ 12 A (220 / 230 / 240 V) 60 $^\circ\text{C}$ 12 A
Rated Operational Current AC-3e (I_e):	(415 V) 60 $^\circ\text{C}$ 12 A (440 V) 60 $^\circ\text{C}$ 12 A (500 V) 60 $^\circ\text{C}$ 12.5 A (690 V) 60 $^\circ\text{C}$ 9 A (380 / 400 V) 60 $^\circ\text{C}$ 12 A (220 / 230 / 240 V) 60 $^\circ\text{C}$ 12 A

Rated Operational Current AC-15 (I_e):	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Operational Current DC-1 (I_e):	(110 V) 1-Pole, 40 °C 15 A (110 V) 1-Pole, 60 °C 15 A (110 V) 1-Pole, 70 °C 15 A (110 V) 2 Poles in Series, 40 °C 27 A (110 V) 2 Poles in Series, 60 °C 27 A (110 V) 2 Poles in Series, 70 °C 24 A (110 V) 3 Poles in Series, 40 °C 27 A (110 V) 3 Poles in Series, 60 °C 27 A (110 V) 3 Poles in Series, 70 °C 24 A (220 V) 2 Poles in Series, 40 °C 15 A (220 V) 2 Poles in Series, 60 °C 15 A (220 V) 2 Poles in Series, 70 °C 15 A (220 V) 3 Poles in Series, 40 °C 27 A (220 V) 3 Poles in Series, 60 °C 27 A (220 V) 3 Poles in Series, 70 °C 24 A (72 V) 1-Pole, 40 °C 27 A (72 V) 1-Pole, 60 °C 27 A (72 V) 1-Pole, 70 °C 24 A (72 V) 2 Poles in Series, 40 °C 27 A (72 V) 2 Poles in Series, 60 °C 27 A (72 V) 2 Poles in Series, 70 °C 24 A (72 V) 3 Poles in Series, 40 °C 27 A (72 V) 3 Poles in Series, 60 °C 27 A (72 V) 3 Poles in Series, 70 °C 24 A
Rated Operational Current DC-3 (I_e):	(110 V) 1-Pole, 40 °C 7 A (110 V) 1-Pole, 60 °C 7 A (110 V) 1-Pole, 70 °C 7 A (110 V) 2 Poles in Series, 40 °C 27 A (110 V) 2 Poles in Series, 60 °C 27 A (110 V) 2 Poles in Series, 70 °C 24 A (110 V) 3 Poles in Series, 40 °C 27 A (110 V) 3 Poles in Series, 60 °C 27 A (110 V) 3 Poles in Series, 70 °C 24 A (220 V) 2 Poles in Series, 40 °C 7 A (220 V) 2 Poles in Series, 60 °C 7 A (220 V) 2 Poles in Series, 70 °C 7 A (220 V) 3 Poles in Series, 40 °C 27 A (220 V) 3 Poles in Series, 60 °C 27 A (220 V) 3 Poles in Series, 70 °C 24 A (72 V) 1-Pole, 40 °C 27 A (72 V) 1-Pole, 60 °C 27 A (72 V) 1-Pole, 70 °C 24 A (72 V) 2 Poles in Series, 40 °C 27 A (72 V) 2 Poles in Series, 60 °C 27 A (72 V) 2 Poles in Series, 70 °C 24 A (72 V) 3 Poles in Series, 40 °C 27 A (72 V) 3 Poles in Series, 60 °C 27 A (72 V) 3 Poles in Series, 70 °C 24 A

Rated Operational Current DC-5 (I_e):	(110 V) 1-Pole, 40 °C 4 A (110 V) 1-Pole, 60 °C 4 A (110 V) 1-Pole, 70 °C 4 A (110 V) 2 Poles in Series, 40 °C 15 A (110 V) 2 Poles in Series, 60 °C 15 A (110 V) 2 Poles in Series, 70 °C 15 A (110 V) 3 Poles in Series, 40 °C 27 A (110 V) 3 Poles in Series, 60 °C 27 A (110 V) 3 Poles in Series, 70 °C 24 A (220 V) 2 Poles in Series, 40 °C 4 A (220 V) 2 Poles in Series, 60 °C 4 A (220 V) 2 Poles in Series, 70 °C 4 A (220 V) 3 Poles in Series, 40 °C 12 A (220 V) 3 Poles in Series, 60 °C 12 A (220 V) 3 Poles in Series, 70 °C 12 A (72 V) 1-Pole, 40 °C 12 A (72 V) 1-Pole, 60 °C 12 A (72 V) 1-Pole, 70 °C 12 A (72 V) 2 Poles in Series, 40 °C 27 A (72 V) 2 Poles in Series, 60 °C 27 A (72 V) 2 Poles in Series, 70 °C 24 A (72 V) 3 Poles in Series, 40 °C 27 A (72 V) 3 Poles in Series, 60 °C 27 A (72 V) 3 Poles in Series, 70 °C 24 A
Rated Operational Current DC-13 (I_e):	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Operational Power AC-3 (P_e):	(400 V) 5.5 kW (415 V) 5.5 kW (440 V) 5.5 kW (500 V) 7.5 kW (690 V) 7.5 kW (380 / 400 V) 5.5 kW (220 / 230 / 240 V) 3 kW
Rated Operational Power AC-3e (P_e):	(415 V) 5.5 kW (440 V) 5.5 kW (500 V) 7.5 kW (690 V) 7.5 kW (380 / 400 V) 5.5 kW (220 / 230 / 240 V) 3 kW
Rated Short-time Withstand Current Low Voltage (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A for 0.1 s 140 A for 1 s 100 A
Maximum Breaking Capacity:	cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 250 A cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 106 A
Rated Insulation Voltage (U_i):	acc. to IEC 60947-4-1 690 V acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Maximum Electrical Switching Frequency:	(AC-1) 600 cycles per hour (AC-15) 1200 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour (DC-13) 900 cycles per hour

Maximum Mechanical Switching Frequency:	3600 cycles per hour
Rated Control Circuit Voltage (U_c):	50 Hz 24 ... 60 V 60 Hz 24 ... 60 V DC Operation 20 ... 60 V
Power Loss:	at 6 A per Pole 0.1 W at Rated Operating Conditions AC-1 per Pole 1 W at Rated Operating Conditions AC-3 per Pole 0.2 W
Operate Time:	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied) :	2 x M4 Screws Placed Diagonally
Connecting Capacity Main Circuit:	Flexible with Ferrule 1/2x 0.75 ... 6 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 4 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 4 mm ² Rigid Stranded 1/2x 1 ... 6 mm ²
Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Connecting Capacity Control Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Wire Stripping Length:	Auxiliary Circuit 10 mm Control Circuit 10 mm Main Circuit 10 mm
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Tightening Torque:	Auxiliary Circuit 1.2 N·m Control Circuit 1.2 N·m Main Circuit 1.5 N·m
Terminal Type:	Screw Terminals
Product Name:	Block Contactor

Technical UL/CSA

NEMA Size:	0
Continuous Current Rating NEMA:	18 A
Horsepower Rating NEMA:	(115 V AC) Single Phase 1 Hp (200 V AC) Three Phase 3 Hp (230 V AC) Single Phase 2 Hp (230 V AC) Three Phase 3 Hp (460 V AC) Three Phase 5 Hp (575 V AC) Three Phase 5 Hp
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
General Use Rating UL/CSA:	(600 V AC) 28 A

Horsepower Rating UL/CSA:	(120 V AC) Single Phase 1 hp (200 ... 208 V AC) Three Phase 3 hp (220 ... 240 V AC) Three Phase 3 hp (240 V AC) Single Phase 2 hp (440 ... 480 V AC) Three Phase 7-1/2 hp (550 ... 600 V AC) Three Phase 10 hp
Connecting Capacity Main Circuit UL/CSA:	Rigid Solid 1/2x 16-10 AWG Rigid Stranded 1/2x 16-10 AWG
Connecting Capacity Auxiliary Circuit UL/CSA:	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Connecting Capacity Control Circuit UL/CSA:	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Tightening Torque UL/CSA:	Auxiliary Circuit 11 in-lb Control Circuit 11 in-lb Main Circuit 13 in-lb
Full Load Amps Motor Use:	(120 V AC) Single Phase 16 A (200 ... 208 V AC) Three Phase 11 A (220 ... 240 V AC) Three Phase 9.6 A (240 V AC) Single Phase 12 A (440 ... 480 V AC) Three Phase 11 A (550 ... 600 V AC) Three Phase 11 A

Environmental

Ambient Air Temperature:	Close to Contactor Fitted with Thermal O/L Relay -25 ... 60 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand:	Category B according to IEC 60947-1 Annex Q
Maximum Operating Altitude Permissible:	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27:	Closed, Shock Direction: B1 25 g Open, Shock Direction: B1 5 g Shock Direction: A 30 g Shock Direction: B2 15 g Shock Direction: C1 25 g Shock Direction: C2 25 g
Resistance to Vibrations:	4g Closed Position & 2g Open position 5 ... 300 Hz
Pollution Degree:	3

Material Compliance

Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
REACH Declaration:	2CMT2021-006202
RoHS Declaration:	2CMT2021-006277
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP:	f65e669b-20d8-43fb-8274-7e2dbb1081c7 China

Simplified SCIP:	f90543cd-ab33-4a07-b542-20643207fdf9 Poland 57112f6f-c541-4141-b3aa-a3476f817b11 Denmark 5ba3fae0-d77c-45e4-a594-b14912751437 Germany ee5dc123-428b-42c2-bf95-bcc7bf7a6f19 Croatia 95079d6e-4b3c-43c8-a92f-dc8f45fdd350 Czechia cada30f6-6e8b-417a-a1fb-79d5576f7acc Germany 610853f9-f761-494d-8feb-c92762c10144 Poland e4cf4642-5ba3-4776-a7c2-c73ada20453d Belgium b6441cab-5123-4844-83ad-99a6ced43f93 Poland 1d064804-a9ea-49be-b30a-146f8e33f26d Netherlands cc7b3f63-6318-429b-bc3a-6e26f3d248e8 Norway 0828aee1-deb6-4361-ad97-15189e90404b Hungary 5d4abeaa-3e53-48d7-abb2-3239364bd15e Hungary 62cfc0d3-8eeb-460b-b46b-a117c0a469f2 Estonia 9aec28df-03d8-4bce-9c6a-c6903713f483 Finland cc82e6c4-5fc9-44ca-b384-289f57c3949e Belgium 9f9596ac-8e6b-4a02-92e0-756818a29633 Bulgaria b279d261-5230-4000-bd99-4069e60ac3a1 Spain f92b3ef9-5a52-498a-8223-436671bd4fff Greece 19b08695-5e7e-4f53-b59d-fe666302cbad Portugal 2aefec57-e310-4d93-a713-f440eacd4fc5 Germany 9858b6d9-3d83-48fe-93fb-5966608c0d68 France ca8f66a9-1353-4d76-9323-c7ab5d89d81d Germany cb589a00-e5bf-4ac0-a0be-3f5f327c3f78 Germany 8e7e3b66-fd47-4540-9a40-54f2c6df496d Sweden 65be4510-7dab-4bee-8358-f3b3e11f3611 Sweden 9fd4dbb7-e2d9-4358-84eb-01bb635d51a4 France
Toxic Substances Control Act - TSCA:	2CMT2023-006525
WEEE B2C / B2B:	Business To Business
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)

ABB EcoSolutions

ABB EcoSolutions:	Yes
ABB Site Meeting Group Waste To Landfill Target:	No non-hazardous waste is sent to a landfill
EcoSolutions Profile:	1SBC100156C0308
End Of Life Disassembling Instructions:	1SBC101080M6801
Environmental Product Declaration - EPD:	1SBD250584E3000
Improved Energy Efficiency for Customers:	Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line
Recyclability Rate of the Product acc. to EN45555:	Design for Closing Resource Loops - Standard EN45555 - 92.7 %

Certificates and Declarations

A2L Certificate – UL:	9AKK108469A4875 9AKK108469A4879
ABS Certificate:	ABS_20-2060694-PDA
BV Certificate:	BV_2634H24898C1
CB Certificate:	CB_SE-117714
CCC Certificate:	CCC_2024010304656669
CQC Certificate:	CQC2010010304445624 CQC2020010304298240

Declaration of Conformity - CCC:	2020980304001253 2020980304001082
Declaration of Conformity - CE:	1SBD250000U1000
Declaration of Conformity - UKCA:	1SBD250031U1000
DNV Certificate:	DNV_TAE00001AF-4
KC Certificate:	KC_HW02016-15005C
LR Certificate:	LRS_LR23403517TA-02
RINA Certificate:	RINA_ELE142224XG
RMRS Certificate:	RMRS_1802705280
UL Certificate:	UL-US-2150887-5 UL-CA-2142658-5
UL Listing Card:	E312527

Container Information

Package Level 1 Units:	box 1 piece
Package Level 1 Width:	87 mm
Package Level 1 Depth / Length:	79 mm
Package Level 1 Height:	47 mm
Package Level 1 Gross Weight:	0.27 kg
Package Level 1 EAN:	3471523110311

External Classifications and Standards

Object Classification Code:	Q
ETIM 7:	EC000066 - Power contactor, AC switching
ETIM 8:	EC000066 - Power contactor, AC switching
ETIM 9:	EC000066 - Power contactor, AC switching
eClass:	V11.0 : 27371003
UNSPSC:	39121529
IDEA Granular Category Code (IGCC):	4758 >> lec Contactors
E-Number (Finland):	3705802
E-Number (Sweden):	3211341

Accessories

Identifier	Description	Type	Qty	Unit Of Measure
1SBN010015R1001	CE5-01D0.1 Auxiliary Contact Block	CE5-01D0.1	1	piece
1SBN010015R1010	CE5-10D0.1 Auxiliary Contact Block	CE5-10D0.1	1	piece
1SBN010016R1001	CE5-01W0.1 Auxiliary Contact Block	CE5-01W0.1	1	piece

1SBN010016R1010	CE5-10W0.1 Auxiliary Contact Block	CE5-10W0.1	1	piece
1SBN010017R1001	CE5-01D2 Auxiliary Contact Block	CE5-01D2	1	piece
1SBN010017R1010	CE5-10D2 Auxiliary Contact Block	CE5-10D2	1	piece
1SBN010018R1001	CE5-01W2 Auxiliary Contact Block	CE5-01W2	1	piece
1SBN010018R1010	CE5-10W2 Auxiliary Contact Block	CE5-10W2	1	piece
1SBN010013R1010	CB5-10 Impulse Contact Block	CB5-10	1	piece
1SBN010013R1001	CB5-01 Impulse Contact Block	CB5-01	1	piece
1SBN010110R1010	CA4-10 Auxiliary Contact Block	CA4-10	1	piece
1SBN010110T1010	CA4-10-T Auxiliary Contact Block	CA4-10-T	1	piece
1SBN010110R1001	CA4-01 Auxiliary Contact Block	CA4-01	1	piece
1SBN010110T1001	CA4-01-T Auxiliary Contact Block	CA4-01-T	1	piece
1SBN010111R1010	CC4-10 Leading Auxiliary Contact Block	CC4-10	1	piece
1SBN010111R1001	CC4-01 Lagging Auxiliary Contact Block	CC4-01	1	piece
1SBN010120R1011	CAL4-11 Auxiliary Contact Block	CAL4-11	1	piece
1SBN010120T1011	CAL4-11-T Auxiliary Contact Block	CAL4-11-T	1	piece
1SBN010140R1322	CA4-22U Auxiliary Contact Block	CA4-22U	1	piece
1SBN010140R1122	CA4-22M Auxiliary Contact Block	CA4-22M	1	piece
1SBN010151R1011	CAT4-11E Auxiliary Contact / Coil Terminal Block	CAT4-11E	1	piece
1SBN010140R1331	CA4-31U Auxiliary Contact Block	CA4-31U	1	piece
1SBN010140R1131	CA4-31M Auxiliary Contact Block	CA4-31M	1	piece
1SBN010151R1111	CAT4-11M Auxiliary Contact / Coil Terminal Block	CAT4-11M	1	piece
1SBN010140R1340	CA4-40U Auxiliary Contact Block	CA4-40U	1	piece
1SBN010140R1113	CA4-13M Auxiliary Contact Block	CA4-13M	1	piece
1SBN010151R1311	CAT4-11U Auxiliary Contact / Coil Terminal Block	CAT4-11U	1	piece
1SBN070156T1000	LDC4 Additional Coil Terminal Block	LDC4	1	piece

1ISBN030105T1000	VM4 Mechanical Interlock Unit	VM4	1	piece
1ISBN081306T1000	BEA16-4 Connecting Link with Manual Motor Starter	BEA16-4	1	piece
1ISBN010140R1104	CA4-04M Auxiliary Contact Block	CA4-04M	1	piece
1ISBN030111R1000	VEM4 Mechanical and Electrical Interlock Set	VEM4	1	piece
1ISBN020112R1000	TEF4-ON Frontal Electronic Timer	TEF4-ON	1	piece
1ISBN020113R1000	TEF4S-ON Frontal Electronic Timer	TEF4S-ON	1	piece
1ISBN010134R1011	CAL4-11K Auxiliary Contact Block	CAL4-11K	1	piece
1ISBN020114R1000	TEF4-OFF Frontal Electronic Timer	TEF4-OFF	1	piece
1ISBN081311R1000	BER16-4 Connection Set for Reversing Contactors	BER16-4	1	piece
1ISBN020115R1000	TEF4S-OFF Frontal Electronic Timer	TEF4S-OFF	1	piece
1ISBN081313R2000	BEY16-4 Connection Set for Star-Delta Starter	BEY16-4	1	piece
1ISBN071303T1000	LY16-4 Connecting Strip	LY16-4	1	piece
1ISBN071305R1000	LF16-4 Connecting Strip	LF16-4	1	piece
1ISBN110108T1000	BX4 Protective Cover	BX4	1	piece
1ISBN072304R1000	LH38-4 Connecting Strip	LH38-4	1	piece
1ISBN040100R1011	WA4-11 24-60V50/60HZ-DC Mechanical Latching Unit	WA4-11	1	piece
1ISBN040100R1014	WA4-14 250-500V50/60HZ-DC Mechanical Latching Unit	WA4-14	1	piece
1ISBN110122T1000	BDT4 Test Block	BDT4	1	piece
1ISBN040100R1010	WA4-10 24VDC Mechanical Latching Unit	WA4-10	1	piece
1ISBN040100R1012	WA4-12 48-130V50/60HZ-DC Mechanical Latching Unit	WA4-12	1	piece
1ISBN060100R1000	RA4 Interface Relay	RA4	1	piece
1ISBN010146R1104	CA4-04MK Auxiliary Contact Block	CA4-04MK	1	piece
1ISBN040100R1013	WA4-13 100-250V50/60HZ-DC Mechanical Latching Unit	WA4-13	1	piece
1ISBN081322R1000	BER16-4KF Connection Set for Reversing Contactors	BER16-4KF	1	piece
1ISBN010146R1113	CA4-13MK Auxiliary Contact Block	CA4-13MK	1	piece
1ISBN081323R2000	BEY16-4KF Connection Set for Star-Delta Starter	BEY16-4KF	1	piece
1ISBN070159T1000	LDC4K Additional Coil Terminal Block	LDC4K	1	piece

1SBN010160R1001	CA4-01K Auxiliary Contact Block	CA4-01K	1	piece
1SBN081314R1000	BEP16-30 Phase to phase connection	BEP16-30	1	piece
1SBN010160R1010	CA4-10K Auxiliary Contact Block	CA4-10K	1	piece
1SBN010146R1122	CA4-22MK Auxiliary Contact Block	CA4-22MK	1	piece
1SBN010160T1001	CA4-01K-T Auxiliary Contact Block	CA4-01K-T	1	piece
1SBN010160T1010	CA4-10K-T Auxiliary Contact Block	CA4-10K-T	1	piece
1SBN030113R1000	VEM4K Mechanical and Electrical Interlock Set	VEM4K	1	piece
1SBN010146R1131	CA4-31MK Auxiliary Contact Block	CA4-31MK	1	piece

Categories

Products > Low Voltage Products and Systems > Control Products > Contactors > Block Contactors > AF Contactors > AF12

