




---

 PRODUCT-DETAILS

## TF42-0.55

### TF42-0.55 Thermal Overload Relay 0.41 ... 0.55 A




---

#### General Information

<b>Extended Product Type:</b>	TF42-0.55
<b>Product ID:</b>	1SAZ721201R1017
<b>EAN:</b>	4013614398025
<b>Catalog Description:</b>	TF42-0.55 Thermal Overload Relay 0.41 ... 0.55 A
<b>Long Description:</b>	The TF42-0.55 thermal overload relay is an economic electromechanical protection device for the main circuit. It offers reliable and fast protection for motors in the event of overload or phase failure. The device has trip class 10. Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP function and a trip indication. The overload relays are connected directly to the block contactors. Single mounting kits are available as accessory.
<b>Display Name:</b>	TF42-0.55

---

#### Ordering

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85364900

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	2CDC106023D0201
<b>Instructions and Manuals:</b>	2CDC106022M6802
<b>Instructions and Manuals (Part 2):</b>	1SAC200017M0002
<b>Ex Operating Instructions:</b>	2CDC106076M6801
<b>Time-Current Characteristic Curve:</b>	1SAZ700506F0006
<b>CAD Dimensional Drawing:</b>	2CDC001079B0201
<b>Dimension Diagram:</b>	1SAZ700405F0001

## Dimensions

<b>Product Net Width:</b>	45 mm
<b>Product Net Height:</b>	88.3 mm
<b>Product Net Depth / Length:</b>	70.5 mm
<b>Product Net Weight:</b>	0.13 kg

## Technical

<b>Setting Range:</b>	0.41 ... 0.55 A
<b>Rated Operational Voltage:</b>	Auxiliary Circuit 600 V AC/DC Main Circuit 690 V AC Main Circuit 600 V DC
<b>Rated Operational Current (<math>I_e</math>):</b>	0.55 A
<b>Rated Frequency (f):</b>	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Main Circuit 50 Hz Main Circuit 60 Hz
<b>Rated Impulse Withstand Voltage (<math>U_{imp}</math>):</b>	Auxiliary Circuit 6 kV Main Circuit 6 kV
<b>Rated Insulation Voltage (<math>U_i</math>):</b>	690 V
<b>Number of Poles:</b>	3P
<b>Number of Auxiliary Contacts NC:</b>	1
<b>Number of Auxiliary Contacts NO:</b>	1
<b>Number of Protected Poles:</b>	3
<b>Conventional Free-air Thermal Current (<math>I_{th}</math>):</b>	Auxiliary Circuit NC 6 A Auxiliary Circuit NO 4 A
<b>Rated Operational Current AC-15 (<math>I_e</math>):</b>	(120 V) NC 3 A (120 V) NO 0.5 A (240 V) NC 3 A (240 V) NO 0.5 A (400 V) NC 0.75 A (400 V) NO 0.5 A (500 V) NC 0.75 A (500 V) NO 0.5 A

<b>Rated Operational Current DC-13 (I<sub>e</sub>):</b>	(125 V) NC 0.55 A (125 V) NO 0.55 A (24 V) NC 1.25 A (24 V) NO 1.25 A (250 V) NC 0.27 A (250 V) NO 0.27 A (500 V) NC 0.15 A (500 V) NO 0.15 A (60 V) NC 0.55 A (60 V) NO 0.55 A
<b>Degree of Protection:</b>	IP20
<b>Pollution Degree:</b>	3
<b>Connecting Capacity Auxiliary Circuit:</b>	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Flexible 1/2x 0.75 ... 1 mm <sup>2</sup> Flexible 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid 1/2x 0.75 ... 4 mm <sup>2</sup>
<b>Connecting Capacity Main Circuit:</b>	Flexible with Ferrule 1/2x 0.75 ... 4 mm <sup>2</sup> Flexible with Insulated Ferrule 1/2x 0.75 ... 4 mm <sup>2</sup> Flexible 1/2x 0.75 ... 4 mm <sup>2</sup> Rigid 1/2x 0.75 ... 4 mm <sup>2</sup>
<b>Tightening Torque:</b>	Auxiliary Circuit 1 ... 1.2 N·m Main Circuit 1.5 ... 2.5 N·m
<b>Wire Stripping Length:</b>	Auxiliary Circuit 9 mm Main Circuit 12 mm
<b>Recommended Screw Driver:</b>	Main Circuit Pozidriv 2
<b>Power Loss:</b>	at Rated Operating Conditions per Pole 1.1 ... 2.0 W
<b>Suitable For:</b>	AF09 AF12 AF16 AF26 AF30 AF38
<b>Standards:</b>	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1 IEC 60335-2-40 A2L

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V AC
<b>Contact Rating UL/CSA:</b>	(NC:) B600 (NC:) Q600 (NO:) Q600 (NO:) D300
<b>Connecting Capacity Main Circuit UL/CSA:</b>	Flexible 1/2x 18-10 AWG Stranded 1/2x 18-10 AWG
<b>Connecting Capacity Auxiliary Circuit UL/CSA:</b>	Flexible 1/2x 18-12 AWG Stranded 1/2x 18-12 AWG
<b>Tightening Torque UL/CSA:</b>	Auxiliary Circuit 9 ... 11 in·lb Main Circuit 13 ... 22 in·lb

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +60 °C Operation Compensated -25 ... +60 °C Storage -50 ... +80 °C
<b>Ambient Air Temperature Compensation:</b>	Yes
<b>Maximum Operating Altitude Permissible:</b>	2000 m
<b>Resistance to Shock acc. to IEC 60068-2-27:</b>	11 ms Pulse 25g
<b>Resistance to Vibrations:</b>	5g 3 ... 150 Hz
<b>RoHS Information:</b>	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
<b>Toxic Substances Control Act - TSCA:</b>	2CMT2023-006525

## Material Compliance

<b>Conflict Minerals Reporting Template (CMRT):</b>	9AKK108467A5658
<b>REACH Declaration:</b>	2CMT2021-006202
<b>RoHS Declaration:</b>	2CMT2021-006277
<b>WEEE B2C / B2B:</b>	Business To Business
<b>WEEE Category:</b>	5. Small Equipment (No External Dimension More Than 50 cm)

## ABB EcoSolutions

<b>ABB EcoSolutions:</b>	Yes
<b>ABB Site Meeting Group Waste To Landfill Target:</b>	UL 2799 Zero Waste To Landfill Validation available
<b>EcoSolutions Profile:</b>	1SFC100125C0355
<b>End Of Life Disassembling Instructions:</b>	1SAC200429H0001
<b>Environmental Information:</b>	1SAC200057H0009
<b>Environmental Product Declaration - EPD:</b>	1SAC200373H0001
<b>Improved Energy Efficiency for Customers:</b>	Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line
<b>Recyclability Rate of the Product acc. to EN45555:</b>	Design for Closing Resource Loops - Standard EN45555 - 65 %

## Certificates and Declarations

<b>A2L Certificate – IEC:</b>	1SAA941000-4601
<b>ABS Certificate:</b>	1SAA941001-0102
<b>ATEX Certificate:</b>	1SAA941010-3901
<b>BV Certificate:</b>	1SAA941001-0203
<b>CB Certificate:</b>	1SAA941009-2001
<b>CCC Certificate:</b>	2024010304658956
<b>CQC Certificate:</b>	CQC2011010309464423

<b>Declaration of Conformity - CCC:</b>	2020980304001788
<b>Declaration of Conformity - CE:</b>	1SAD101100-3503
<b>Declaration of Conformity - UKCA:</b>	1SAD201100-3503
<b>DNV GL Certificate:</b>	1SAA941001-0302
<b>EAC Certificate:</b>	1SAA941002-2701
<b>GL Certificate:</b>	1SAA941007-0401
<b>IECEX Certificate:</b>	1SAA941003-4001
<b>LR Certificate:</b>	1SAA941001-0502
<b>RINA Certificate:</b>	1SAA941000-0802
<b>RMRS Certificate:</b>	1SAA941000-0704
<b>UL Certificate:</b>	E48139-20090126

## Container Information

<b>Package Level 1 Units:</b>	carton 1 piece
<b>Package Level 1 Width:</b>	48 mm
<b>Package Level 1 Height:</b>	92 mm
<b>Package Level 1 Depth / Length:</b>	78 mm
<b>Package Level 1 Gross Weight:</b>	0.145 kg
<b>Package Level 1 EAN:</b>	4013614398025
<b>Package Level 2 Units:</b>	carton 40 piece
<b>Package Level 2 Width:</b>	280 mm
<b>Package Level 2 Height:</b>	210 mm
<b>Package Level 2 Depth / Length:</b>	395 mm
<b>Package Level 2 Gross Weight:</b>	7.346 kg
<b>Package Level 2 EAN:</b>	4013614440069

## External Classifications and Standards

<b>Object Classification Code:</b>	F
<b>ETIM 9:</b>	EC000106 - Thermal overload relay
<b>ETIM 10:</b>	EC000106 - Thermal overload relay
<b>eClass:</b>	V11.0 : 27371501
<b>UNSPSC:</b>	39122330
<b>IDEA Granular Category Code (IGCC):</b>	5366 >> Thermal overload relay
<b>E-Number (Finland):</b>	3706115
<b>E-Number (Norway):</b>	4116756
<b>E-Number (Sweden):</b>	3211959

## Accessories

Identifier	Description	Type	Qty	Unit Of Measure
------------	-------------	------	-----	-----------------

1SAZ701902R0001	DB42 Single Mounting Kit DB42		1	piece
1SAX101911R1001	DRS-F-01 Remote Reset Coil	DRS-F-01	1	piece
1SAX101911R1002	DRS-F-02 Remote Reset Coil	DRS-F-02	1	piece
1SAX101911R1003	DRS-F-03 Remote Reset Coil	DRS-F-03	1	piece
1SAX101911R1004	DRS-F-04 Remote Reset Coil	DRS-F-04	1	piece
1SAZ701904R1001	DRS-F-TF-01 Remote Coil	DRS-F-TF-01	1	piece
1SAZ701904R1002	DRS-F-TF-02 Remote Coil	DRS-F-TF-02	1	piece
1SAZ701904R1003	DRS-F-TF-03 Remote Coil	DRS-F-TF-03	1	piece
1SAZ701904R1004	DRS-F-TF-04 Remote Coil	DRS-F-TF-04	1	piece
1SAZ701903R1001	WRH-F Holder	WRH-F	1	piece
1SAZ701903R1011	WRB-400 Bowden Wire	WRB-400	1	piece
1SAZ701903R1012	WRB-600 Bowden Wire	WRB-600	1	piece
1SAZ701903R1013	WRB-1000 Bowden Wire	WRB-1000	1	piece
1SAZ701903R1030	WRBG Gasket	WRBG	1	piece
1SFA616162R1014	KPR3-101L Reset push button	KPR-101L	1	piece

## Categories

Products > Low Voltage Products and Systems > Control Products > Contactors > Thermal Overload Relays

Parts & Services > Drives > Services > Spares and Consumables > Parts

