



PRODUCT-DETAILS

XT1B 160 TMD 40-450 3p F F

XT1B 160 TMD 40-450 3p F F



General Information	
Extended Product Type:	XT1B 160 TMD 40-450 3p F F
Product ID:	1SDA066803R1
EAN:	8015644003302
Catalog Description:	XT1B 160 TMD 40-450 3p F F
Long Description:	C.BREAKER TMAX XT1B 160 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 40-450 A
Display Name:	XT1B 160 TMD 40-450 3p F F

ABB EcoSolutions	
ABB EcoSolutions:	Yes
ABB Site Meeting Group Waste To Landfill Target:	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions:	9AKK108468A2347
Environmental Product Declaration - EPD:	9AKK108468A1890 9AKK108468A7793
Extended Product Lifetime:	Product Modularity

Recyclability Rate of the Product acc. to EN45555: Design for Closing Resource Loops - Standard EN45555 - 55.9 %

Material Compliance

REACH Declaration:	9AKK108466A1425
RoHS Declaration:	9AKK108466A1424
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
Toxic Substances Control Act - TSCA:	9AKK108467A8326
SCIP:	5cab19a8-a211-40c5-bc9a-598007736c08 Italy
Simplified SCIP:	abcf1fa6-993f-40bd-948e-7031a129c6fd Spain 2909f5f6-ef26-4852-a421-00343f2a1bf8 Belgium 235f26cb-78ea-4142-86a8-40c6d9269936 Czechia b696f5da-3bb1-4927-8e16-fbeb5af0d012 Hungary d0e32a4a-d6ae-4037-9851-caeccd49d0d1 France bb77a6d6-2708-474c-9f92-8318a5904431 Germany 617944fc-cc3f-4139-be4e-7081dda306fe Sweden 55adadea-3c4a-42ca-8e5b-951e0b147e82 Germany a7a3ee97-4148-4339-8171-d93ccb74797e Denmark f9f02b49-3f65-40ed-8d49-47307e1ed2cc Germany 67490311-ba58-4d42-b7a3-a1906ce91f7d Germany f99a2448-1391-42bf-a0b1-c2bc741303dd Croatia edb092a4-db53-4f4d-ac32-e7197c9fc30f Sweden 29bd069c-9cf7-451d-a67b-e19c26a6024f Netherlands 52315325-7b94-42a9-a354-6b77d2f4ecb3 Poland 8a890085-a4df-4f26-8327-093b43f9d1c2 Bulgaria f66a5efb-a803-42ba-866b-e1fecc118301 Norway 6133c899-40e7-4adc-8cd3-cfd3163257c9 Germany c6867efd-1d68-44fd-830a-c3cbfac0122a Portugal 8650c8bf-2467-49e7-9e5a-2a12ae456925 Poland bad829f3-7ca9-408f-b042-c31ab585e58e Greece c3fa5ce2-5f63-4b2e-a6c1-0b728aa19a97 France afa820e1-182b-4046-a65a-c721fbd0877f Estonia f2d51ade-ddb7-40d4-bc3f-bf975ca32912 Belgium 00ad4c8c-baf2-406d-aec8-f7ce17297da9 Hungary ecb413a7-766a-4b40-8eef-164b819c6b12 Poland 241539ed-acf4-4841-92dd-cb32075995b6 Finland

Environmental

Environmental Information:	9AKK108467A6707
-----------------------------------	-----------------

Ordering

Order Code US and Canada:	XT1BE3040AFF000XXX
E-Number (Finland):	3638025
E-Number (Norway):	4309604
EAN:	8015644003302
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	76.2 mm
Product Net Height:	130 mm
Product Net Depth / Length:	70 mm
Product Net Weight:	1.1 kg

Container Information

Package Level 1 Units:	box 1 piece
Package Level 1 Width:	128 mm
Package Level 1 Height:	135 mm
Package Level 1 Depth / Length:	143 mm
Package Level 1 Gross Weight:	1.124 kg
Package Level 1 EAN:	8015644003302

Additional Information

Circuit Breaker Type to be Associated:	Power Distribution
Product Main Type:	SACE Tmax XT
Product Name:	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker
Version:	F
CAD Dimensional Drawing:	1SDH001295R0008

Technical

Connecting Capacity Main Circuit:	Busbar 45.5 ... 80 mm ²
Current Type:	AC/DC
Electrical Durability:	120 cycles per hour 8000 cycle
Mechanical Durability:	240 cycles per hour 25000 cycle
Number of Poles:	3P
Opening Time:	CB with SOR 30 ms CB with UVR 30 ms
Order Multiple:	1 piece
Power Loss:	at Rated Operating Conditions per Pole 2.6 W
Rated Current (I _n):	40 A
Rated Frequency (f):	50 / 60 Hz
Rated Impulse Withstand Voltage (U _{imp}):	8 kV

Rated Instantaneous Short-Circuit Current Setting (I_i): 450 A

Rated Insulation Voltage (U_i):	800 V
Rated Operational Voltage:	690 V AC 500 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 25 kA (230 V AC) 25 kA (240 V AC) 25 kA (380 V AC) 18 kA (415 V AC) 18 kA (440 V AC) 11.25 kA (500 V AC) 8 kA (525 V AC) 6 kA (690 V AC) 3 kA (250 V DC) 2 Poles in Series 18 kA (500 V DC) 3 Poles in Series 18 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 25 kA (230 V AC) 25 kA (240 V AC) 25 kA (380 V AC) 18 kA (415 V AC) 18 kA (440 V AC) 15 kA (500 V AC) 8 kA (525 V AC) 6 kA (690 V AC) 3 kA (250 V DC) 2 Poles in Series 18 kA (500 V DC) 3 Poles in Series 18 kA
Rated Uninterrupted Current (I_u):	160 A
Rated Voltage (U_r):	690 V
Recommended Screw Driver:	Main Circuit M6
Release:	TMD
Release Type:	TM
Setting Range:	28...40 A
Short-Circuit Performance Level:	B
Standards:	IEC60947-2
Sub-type:	XT1
Terminal Connection Type:	Front
Terminal Type:	Bolt
Tightening Torque:	6 N·m

Certificates and Declarations

ATEX Certificate:	No certification needed
Data Sheet, Technical Information:	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE:	9AKK106713A5532
GL Certificate:	1SDL000163R0103
LR Certificate:	1SDL000163R0100
UL Certificate:	No certification needed
VDE Certificate:	No certification needed
Dimension Diagram:	1SDH000719R0100
Mechanical Drawings:	1SDH000719R0100

Wiring Diagram:	1SDM000068R0001
Instructions and Manuals:	1SDH000719R0001

External Classifications and Standards	
ETIM 9:	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 10:	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code:	Q
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
eClass:	V11.1 : 27370409

Accessories				
Identifier	Description	Type	Qty	Unit Of Measure
1SDA066305R1	ADP MONT. FIXED TERM. PF XT1 3p	xADP MONT. FIXED TERM. PF XT1 3p	x1	piece
1SDA066865R1	KIT EF XT1 3pcs	KIT EF XT1 3pcs	1	piece
1SDA066867R1	KIT EF XT1 6pcs	KIT EF XT1 6pcs	1	piece
1SDA066260R1	KIT EF FP XT1 3pcs	KIT EF FP XT1 3pcs	1	piece
1SDA066889R1	KIT ES XT1 3pcs	KIT ES XT1 3pcs	1	piece
1SDA066891R1	KIT ES XT1 6pcs	KIT ES XT1 6pcs	1	piece
1SDA066957R1	KIT FB XT1 3pcs	KIT FB XT1 3pcs	1	piece
1SDA066959R1	KIT FB XT1 6pcs	KIT FB XT1 6pcs	1	piece
1SDA066905R1	KIT FC Cu XT1 3pcs	KIT FC Cu XT1 3pcs	1	piece
1SDA066907R1	KIT FC Cu XT1 6pcs	KIT FC Cu XT1 6pcs	1	piece
1SDA067151R1	KIT FC CuAl 1x1,5...70mm2 XT1 3pcs	KIT FC CuAl 1x1,5...70mm2 XT1 3pcs	1	piece
1SDA067153R1	KIT FC CuAl 1x1,5...70mm2 XT1 6pcs	KIT FC CuAl 1x1,5...70mm2 XT1 6pcs	1	piece
1SDA067155R1	KIT FC CuAl 1x35...95mm2 XT1 3pcs	KIT FC CuAl 1x35...95mm2 XT1 3pcs	1	piece
1SDA067157R1	KIT FC CuAl 1x35...95mm2 XT1 6pcs	KIT FC CuAl 1x35...95mm2 XT1 6pcs	1	piece
1SDA067159R1	KIT FC CuAl 1x120...240mm2 XT1 3pcs +ADP	KIT FC CuAl 1x120...240mm2 XT1 3pcs +ADP	1	piece
1SDA067161R1	KIT FC CuAl 1x120...240mm2 XT1 6pcs +ADP	KIT FC CuAl 1x120...240mm2 XT1 6pcs +ADP	1	piece
1SDA066921R1	KIT MC CuAl 6x2.5...35mm2 XT1 3pcs	KIT MC CuAl 6x2.5...35mm2 XT1 3pcs	1	piece
1SDA066923R1	KIT MC CuAl 6x2.5...35mm2 XT1 6pcs	KIT MC CuAl 6x2.5...35mm2 XT1 6pcs	1	piece
1SDA066937R1	KIT R XT1 3pcs	KIT R XT1 3pcs	1	piece
1SDA066939R1	KIT R XT1 6pcs	KIT R XT1 6pcs	1	piece
1SDA066664R1	HTC XT1 3p TERMINAL COVERS HIGH 2pcs	HTC XT1 3p TERMINAL COVERS HIGH 2pcs	1	piece

1SDA066655R1	LTC XT1 3p TERMINAL COVERS LOW 2pcs	LTC XT1 3p TERMINAL COVERS LOW 2pcs	1	piece
1SDA068954R1	PB 90mm FP 6pcs XT1..XT4 4p KIT DI.PH.RE	PB 90mm FP 6pcs XT1..XT4 4p KIT DI.PH.RE	1	piece
1SDA066652R1	KIT DIN50022 XT1 3p PLATE DIN	KIT DIN50022 XT1 3p PLATE DIN	1	piece
1SDA066268R1	KIT R FP XT1 3pcs	KIT R FP XT1 3pcs	1	piece
1SDA067122R1	RC Inst HV 85...690Vac XT1 3p F	RC Inst HV 85...690Vac XT1 3p F	1	piece
1SDA067123R1	RC Sel HV 85...690Vac XT1 3p F	RC Sel HV 85...690Vac XT1 1 3p F		piece

Categories

Products > Low Voltage Products and Systems > Circuit Breakers > Moulded Case Circuit Breakers > Tmax XT

