



 PRODUCT-DETAILS

XLP2

XLP2 Fuse Switch Disconnecter



General Information

Extended Product Type:	XLP2
Product ID:	1SEP101892R0001
EAN:	7025840016861
Catalog Description:	XLP2 Fuse Switch Disconnecter
Long Description:	XLP2,3-pole,400A, without clamps or bolts
Display Name:	XLP2

ABB EcoSolutions

ABB EcoSolutions:	Yes
ABB Site Meeting Group Waste To Landfill Target:	No non-hazardous waste is sent to a landfill UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions:	9AKK108469A3432
Environmental Product Declaration - EPD:	9AKK108468A2201 9AKK108468A2281
Recyclability Rate of the Product acc. to EN45555:	Design for Closing Resource Loops - Standard EN45555 - 94.1 %

Material Compliance

Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
REACH Declaration:	1SCC011021D0201
RoHS Declaration:	1SCC011020D0201
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Popular Downloads

Data Sheet, Technical Information:	1SEC312012D0201
Instructions and Manuals:	No Instructions and Manuals needed

Environmental

Degree of Protection:	IP30
------------------------------	------

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099
Country of Origin:	Bulgaria China

Dimensions

Product Net Width:	210 mm
Product Net Height:	290 mm
Product Net Depth / Length:	130 mm
Product Net Weight:	2.3 kg

Container Information

Package Level 1 Units:	shrink-wrap 1 piece
Package Level 1 Width:	210 mm
Package Level 1 Depth / Length:	130 mm
Package Level 1 Height:	290 mm
Package Level 1 Gross Weight:	2.5 kg
Package Level 1 EAN:	7025840016861
Package Level 2 EAN:	7025840016861

Technical

Device Type Manager (DTM):	Fuseswitchdisconnector
Electronic Fuse Monitoring:	No
Fuse Size:	NH2
Fuse System:	DIN
Handle Type:	Front Cover 3P
Mounting Type:	Baseplate
Number of Poles:	3P
Power Loss:	at Rated Load 13 W
Rated Conditional Short-Circuit Current (I_{nc}):	(690 V) 50 kiloampere rms
Rated Current (I_n):	400 A
Rated Frequency (f):	Main Circuit 50/60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 8 kV
Rated Operational Current AC-21B (I_e):	(690 V) 315 A
Rated Operational Current AC-22B (I_e):	(500 V) 400 A (800 V) 400 A
Rated Operational Voltage:	500 V AC 690 V AC
Rated Voltage (U_r):	500 V AC 690 V AC
Special Functions:	Not Included
Standards:	IEC60947-3 GB/T14048.3
Terminal Type:	Lug terminals

Certificates and Declarations

Declaration of Conformity - CE:	1SEP500050P0001
--	-----------------

External Classifications and Standards

Object Classification Code:	S
ETIM 9:	EC001040 - Fuse switch disconnector
ETIM 10:	EC001040 - Fuse switch disconnector
eClass:	V11.1 : 27371401
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Sweden):	3171956

Categories

Products > Low Voltage Products and Systems > Fusegear > Fuse Switch Disconnectors > EasyLine

