



 PRODUCT-DETAILS

XLP00-6BC

XLP00-6BC Fuse Switch Disconnecter



General Information

Extended Product Type:	XLP00-6BC
Product ID:	1SEP101890R0002
EAN:	7025840013402
Catalog Description:	XLP00-6BC Fuse Switch Disconnecter
Long Description:	XLP00,3-pole,160A, incl. 6 Bridge Clamps
Display Name:	XLP00-6BC

ABB EcoSolutions

ABB EcoSolutions:	Yes
ABB Site Meeting Group Waste To Landfill Target:	No non-hazardous waste is sent to a landfill UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions:	9AKK108469A3432
Environmental Product Declaration - EPD:	9AKK108468A2201 9AKK108468A2281
Recyclability Rate of the Product acc. to EN45555:	Design for Closing Resource Loops - Standard EN45555 - 94.1 %

Material Compliance

Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
REACH Declaration:	1SCC011021D0201
RoHS Declaration:	1SCC011020D0201
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Popular Downloads

Data Sheet, Technical Information:	1SEC312012D0201
Instructions and Manuals:	1SEC312012D0201

Environmental

Degree of Protection:	IP30
------------------------------	------

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099
Country of Origin:	Bulgaria China

Dimensions

Product Net Width:	105 mm
Product Net Height:	187 mm
Product Net Depth / Length:	90 mm
Product Net Weight:	0.57 kg

Container Information

Package Level 1 Units:	shrink-wrap 1 piece
Package Level 1 Width:	105 mm
Package Level 1 Depth / Length:	90 mm
Package Level 1 Height:	187 mm
Package Level 1 Gross Weight:	0.63 kg
Package Level 1 EAN:	7025840013402
Package Level 2 EAN:	detach

Technical

Device Type Manager (DTM):	Fuseswitchdisconnector
Electronic Fuse Monitoring:	No
Fuse Size:	NH00 NH000
Fuse System:	DIN
Handle Type:	Front Cover 3P
Mounting Type:	Baseplate
Number of Poles:	3P
Power Loss:	at Rated Load 3.5 W
Rated Conditional Short-Circuit Current (I_{nc}):	(690 V) 50 kiloampere rms
Rated Current (I_n):	160 A
Rated Frequency (f):	Main Circuit 50/60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 8 kV
Rated Operational Current AC-21B (I_e):	(690 V) 125 A
Rated Operational Current AC-22B (I_e):	(500 V) 160 A (800 V) 63 A (1000 V) 125 A
Rated Operational Current AC-23B (I_e):	(400V) 125 A
Rated Operational Voltage:	400 V AC 500 V AC 690 V AC 800 V AC 1000 V AC
Rated Voltage (U_r):	400 V AC 500 V AC 690 V AC 800 V AC 1000 V AC
Special Functions:	Not Included
Standards:	IEC60947-3 GB/T14048.3
Terminal Type:	Cable Clamp

Certificates and Declarations

Declaration of Conformity - CE:	1SEP500050P0001
--	-----------------

External Classifications and Standards

Object Classification Code:	S
ETIM 9:	EC001040 - Fuse switch disconnector
ETIM 10:	EC001040 - Fuse switch disconnector
UNSPSC:	39121600

eClass:	V11.1 : 27371401
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland):	3601019
E-Number (Norway):	1687108
E-Number (Sweden):	2307311

Categories

Products > Low Voltage Products and Systems > Fusegear > Fuse Switch Disconnectors > EasyLine

